

S6X & S5X Outdoor Access



Features

- Waterproof, conforms to IP67
- Strong Zinc Alloy Electroplated anti-vandal case
- Full programming from the keypad
- 2000 uses, supports Card, 4-8 Digit PIN, Card + PIN
- Stand alone keypad or Wiegand 26 output for connection to a controller
- Backlight keys with LEDs display for status
- Adjustable Door Output time, Alarm time, Door Open time
- Very low power consumption (40mA)
- Fast operating speed, <20ms with 2000 users
- Lock output current short circuit protection
- Easy to install and program
- Built in light dependent resistor (LDR) for anti tamper & buzzer

Specifications

Operating Voltage	DC 10V-24 ±10%
Working Mode	Pulse Mode, Toggle Mode
Wiegand	WG26 Output/Input, PIN Virtual card number output
User Capacity	2000
Card Reading Distance	3-6 cm
Active Current	<80mA
Idle Current	40±5 mA
Lock & Alarm Output Load	Max 2A/1A
Operating Temperature /Humidity	-40~70°C; 10%- 98% RH
Environment	Conforms to IP67
Adjustable Door Relay time	0 -99 seconds
Adjustable Alarm Time	0- 3 minutes
Wiring Connections	Electric Lock, Exit Button, External Alarm
Dimensions S5XD	L110xW76xH22mm(Wide)
Dimensions S6XD	L129xW44xH20mm(Slim)