

Access control Manufacture

Metal waterproof access control system

Product features

- ◆ Working voltage: DC9V-28V
- ◆ Waterproof degree: IP68
- ◆ With Anti-theft alarm output for external alarm device.
- ◆ With built-in anti-theft equipments.
- ◆ Support enrolling cards continuously
- ◆ Perfect design, with backlight and fashion silver finish.
- ◆ Waterproof design for outdoor use.
- ◆ strong standalone function device, can be used as WG26 reader alone.
- ◆ Capacity: 2000 user's cards, 2000 codes;
- ◆ Access ways : cards ,code ,card +code.
- ◆ Low power :static current less than 30mA.
- ◆ Support only keypad ,
- ◆ users can reset private passwords.
- ◆ Search fast less than 0.1s .
- ◆ Wiegand output W26 for card and W34 for codes.
- ◆ use keypad to delete lost cards for safety.
- ◆ Short-circuit protect : when relay or alarm output short circuit, it will shut up output in 100 μ S.

Technical parameters

Environment Temperature: -45°C ~60°C
Environment Humidity: 10%~90%
Electric lock output: $\leq 3A$
Alarm output: $\leq 20A$
Output short-circuit protection time: $\leq 100\mu S$
Open-door time: 0 ~ 99 seconds (adjustable)
Size: 120 *56*18mm

Products types

Model no	Card style	frequency	Reading range
EM Access	EM	125KHz	5-15cm
MF Access	MIFARE	13.56KHz	3-10cm
EM-W Access	EM	125KHz	5-15cm
MF-W Access	MIFARE	13.56KHz	3-10cm

CE FC 
ISO9001:2000

